








Performance Series Battery Specifications

MODEL	Voltage	PHCA** (5 sec.)	CCA*	HCA	MCA	Nominal Capacity		Reserve Capacity Minutes	Length inches (mm)	Width inches (mm)	Height inches (mm)	Weight lbs (kg)	Terminal	Torque Specs in-lbs (Nm max)	Internal Resistance (mΩ)	Short Circuit Current
						(20 Hr Rate- Ah)	(10 Hr Rate- Ah)									
 75/86-705	12	1100	708	875	760	49	45	89	9.44 (239.8)	7.00 (177.8)	7.92 (201.2)	43.4 (19.7)	SAE, Side 3/8-16" Receptacle	60 (6.8)	2.8	2200
 48-720	12	1250	723	950	842	69	63	130	10.91 (277.1)	6.85 (174.0)	7.47 (189.7)	48 (21.8)	SAE	60 (6.8)	2.8	2300
 34-790	12	1500	792	1200	990	61	57	114	10.82 (274.8)	6.76 (171.7)	7.84 (199.1)	46.6 (21.1)	SAE	60 (6.8)	2.9	2400
 34R-790	12	1500	792	1200	990	61	57	114	10.82 (274.8)	6.76 (171.7)	7.84 (199.1)	46.6 (21.1)	SAE, Positive Right Terminal	60 (6.8)	2.9	2400
 78-790	12	1500	792	1200	990	61	57	114	10.82 (274.8)	7.00 (177.8)	7.36 (186.9)	47.1 (21.4)	SAE, Side 3/8-16" Receptacle	60 (6.8)	2.9	2400
 65-760	12	1500	762	1200	891	64	59	129	11.83 (300.5)	7.18 (182.4)	7.38 (187.5)	49.8 (22.6)	SAE	60 (6.8)	2.3	2500
 31-800	12	1600	802	1380	1188	99	94	188	13.0 (330.2)	6.78 (172.2)	9.42 (239.3)	69.0 (31.3)	SAE or 3/8-16" Stud	200 (22.6)	2.6	2600